



ITEM	Hoshizaki Undercounter Refrigerator
MODEL	RT-158MA-T
POWER SUPPLY	1 Phase 220V ~ 60Hz Capacity: 0.55kVA (2.51A)
AMPERAGE	Rated 2.00A
ELECTRIC CONSUMPTION	245W Heater 189W Defrost 165W
HEAT REJECTION	-
POWER CORD	2.0m (Plug with Earth Wire)
EFFECTIVE CAPACITY	420L
OUTSIDE DIMENSIONS	1500mm (W) x 750mm (D) x 800(790-820) mm (H)
INSIDE DIMENSIONS	1140mm (W) x 586mm (D) x 599mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom) ABS Plastic (Top & Bottom on Door)
INTERIOR	Stainless Steel, ABS Plastic (Door)
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic
CONDENSER	Wire and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -6 to 12°C
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
LEG	Plastic Adjustable 90 to 120mm
SHELF	-
WEIGHT	Net: 90kg (Gross: Approx. 110kg)
PACKAGE	Carton 1565mm (W) x 830mm (D) x 790mm (H)
ACCESSORIES	RAIL
OPERATING CONDITIONS	Ambient Temperature: 5-43°C Voltage Range: Rated Voltage±6%

\*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 38°C and power supply of 220V 60Hz. The amperage and electric consumption are based on measurements at ambient temperature of 38°C and power supply of 220V 60Hz.
3. The cabinet temperature range of -6 to 12°C is guaranteed at ambient temperature of 35°C.
4. Product code: T269-D005(HTW)

# HOSHIZAKI UNDERCOUNTER REFRIGERATOR RT-158MA-T

APPROVED LIU	CHECKED WANG	DESIGNED WANG	DRAWN JIN	SCALE 1/20	TRIGONOMETRY
APPROVED	DESIGNED	SYMBOL	DATE 2021.6.16	DRAWING NO. D*****	SYMBOL