## HOSHIZAKI



Code:	Touch Screen Hood Type Dishwasher	Model:
071T.1111AH.EB		HW-600B PDRT











#### **MAIN FEATURES**

- \* Userfriendly touch screen panel
- \* Easy to follow washing steps with dynamic and coloured screen
- \* Stainless steel body including washing and boiler tank.
- \* Monoblock hygenic washing tank.
- \* 69/35/27/23/18 racks per hour (Rack dimensions 50X50 cm)
- \* 2.3 It water consumption per cycle
- \* On-screen easy-to-failure status monitoring
- \* Digital Pressure switch for washing tank
- \* Adjustable detergent / Rinse aid time from screen panel
- \* Non-returned check valve system
- \* Saves energy, detergent and water
- \* Easy start-up: Single button for water filling and heating in the boiler tank.
- \* Adjustable feet for height optimization
- \* The dishwasher is completely sealed to guarantee IPX5 water protection
- \* Electrical components and cabling according to international standards and safety regulations
- \* Washing and rinsing temperatures thermo-stop controlled.
- \* Contais stainless steel tank filter
- $* \quad \mbox{Touch screen for temperatures and error displays.} \\$
- \* Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C)
- \* Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C

## **OPTIONS**

### ACCESSORIES

- \* Electrical Connection Cable, Flexible Water Supply and Drain Hose
- \* 3 Baskets Promotional (Plate, Glass, and Cutlery)
- \* Detergent Dispenser
- Rinse Aid Dispenser
- \* Drain Pump
- \* Rinsing Pump


### **STANDARDS**


- \* EN 60335-1 European Standard relating to safety of household and similar electrical appliances
- \* EN 60335-2-58 European Standard relating to the safety of electric appliances


# HOSHIZAKI




Code:	Taush Coman Hand Toma Dishumshan	Model:
071T.1111AH.EB	Touch Screen Hood Type Dishwasher	HW-600B PDRT









DIMENSIONS (Net)		DIME	DIMENSIONS (Shipping)		
* Width (mm):	707	* Width (mm):	725		
* Depth (mm):	779	* Depth (mm):	795		
* Height (mm):	1485 ( 1960 )	* Height (mm):	1638		
* Weight (kg):	110 ( +/- 10 )	* Weight (kg):	120		
		* Volume (m³):	0,94		

		* Volume (m³):	0,94				
TECHNICAL SPECIFICATIONS							
<ul><li>Washing Capacity</li><li>(Basket/hr):</li></ul>	69/35/27/23/18	* Electric	3,41 Kw 220 V 60 Hz				
<ul><li>* Washing Tank Capacity:</li><li>* Boiler Tank Capacity:</li></ul>	22 lt 7 lt	consumption:	3,96 Kw 240 V 60 Hz				
* Washing Pump Power:	0,66 kW	WATER-IN					
* Rinsing Pump Power:	0,25 kW	* Cold water inlet:	3/4 inch				
* Washing Heat power:	1,8 kW ( 220 V )	* Hot Water Inlet:	3/4 inch				
	2,2 kW ( 240 V )	* Water inlet pressure	2-4 Bar				
* Rinsing Heat power:	2,75 kW ( 220 V )	DRAIN					
* Max. Noise:	3,3 kW ( 240 V ) 67 dBA	* Dirty water discharge connection:	3/4 inch (Ø28 mm)				
* Loading Height:	445 mm	Protection class:	IPX5				